NCR SelfServ™ 82

INTERIOR FREESTANDING MULTI-FUNCTION INTERACTIVE TELLER ATM



KEY VALUES

- Transform Ready out of the box to work with NCR Interactive Teller Assisted Service Software, enabling efficient delivery of convenient live teller service across extended hours and locations
- Attract Infinity Display: supports multi-touch. 15" or 19" LCD screen. Integrated customized branding opportunities for financial institutions.
- Engage Supports NCR CxBanking SW platform includes personalization and targeted marketing opportunities. Enable the omni-channel experience. Engage mobile first consumers.
- **Available** Enhanced ATM module reliability via Media Handling 2.0. Flexible, future-proofed dispense, deposit and recycling options. Performance enhanced durable design.
- Manage Service intervention process improvements. Full range of common parts across all solutions. Improved device level intelligence.
- Secure Security designed in for more effective risk management and fraud prevention. Includes: strengthened shutter, cash/consumer camera and new flush SPS card reader.

It's not just what it does. It's what it does for you.















TECHNICAL SPECIFICATIONS

LIVE TELLER TRANSACTIONS

Extend opening hours and increase service availability with:

- Instant check cashing
- Depositing to multiple accounts in one transaction
- · Card or Cardless authentication, e.g., ID and signature
- Bill payments
- Account to account transfers
- Customer service inquiries
- · Remote Teller driven new account opening
- Loan initiation
- Advice and assistance from a live person

PRODUCT DIMENSIONS

 HEIGHT 64.21" (1,631mm) WIDTH 30.31" (770mm) DEPTH 40.59" (1,031mm)

WFIGHT

1,830lbs (830kg) CEN I safe CEN III 1,984lbs (900kg) **CEN IV** 2,105lbs (955kg)

CONSUMER INTERFACE

- Infinity Display Supports multi-touch. 15" or 19" brightened color LCD screen
- Media Entry/Exit Indicators Dynamic active customizable color LEDs. Directional and pulsing user guidance MEEIs
- · Lighting Task Lighting. Ambient light sensing
- PIN Pad Recessed Encrypting (Polycarbonate or stainless steel)
- Card Reader EMV Ready. (Dip, Motorized IMCRW)
- Contactless enabled Integrated Reader (via card, smartphone or smartwatch)

- Audio Public/Private. Enhanced speakers. Noise cancelling microphone
- Video camera and Video capture card
- On screen signature capture support
- · Photo ID scanner

MEDIA HANDLING 2.0 TECHNOLOGY

- Dispense S2 Media Dispense Module: up to 60 note bunch, 2,500 notes per cassette*. Up to 25,000 note capacity (5 high)** Vacuum based with adaptive media picking technology
- Deposit SDM2: up to 100 mixed media bunch cash + check in a single transaction. Store up to 4,000 notes + 400 checks* 4-way bundle orientation. Two storage variants
- Recycle/Deposit GBxx2: up to 200 notes per transaction. Store up to 2,300 notes per cassette (deposit). Up to 2,000 notes (recycle)* Enhanced note pre-acceptor and separator

PRINTERS

• Thermal Receipt/Journal Printer, options - Dual roll and 2ST

SECURITY

- Supports "Picture in Picture" security
- Privacy filter enabled display
- Cameras 3rd party consumer camera and optional cash slot camera enabled
- SolidCore Software Suite for APTRA™
- Trusted Platform Module enabled
- Strengthened Secure Shutter (SSS)
- Integrated "flush" Skimming Protection Solution (SPS)
- UL437 Topbox Lock
- Safes CEN I, CEN III, CEN III GasEx, CEN IV GasEx options

ENVIRONMENTAL

- Standard 50°F to 104°F (10°C to 40°C)
- Humidity 20% to 80%
- Acoustics 65dB (A) idle 68dB operating. Max 75dB (A) fan

SERVICING

- Front/rear/side access
- LCD Operator Panel (GOP or COP) rear load only
- State of health indicators across all modules

OPERATING PLATFORM

- PC Core with Intel® i5 processor.
- 8GB RAM. 240GB Solid State Hard Drive
- DVD-RW Drive

SOFTWARE

- Microsoft Windows® 7 Professional / Windows® 10 ready
- NCR APTRA™ XFS
- Supports NCR CxBanking SW platform
- NCR Interactive Teller Enterprise Software client
- NDC standard edition (SMI) configuration only

ADDITIONAL FEATURES -FUTURES ENABLED

- Barcode Reader 2D Barcode supports 1D/2D documents
- e-Receipts to a mobile device
- UPS (Uninterruptable Power Supply)
- *Dependent on check or note quality, thickness and deposit module used. Capacity may vary by country, currency type, condition and quality of notes
- ** 5 High Dual-dispense note that ATM is slightly higher by approximately 100mm.

WHY NCR?

life easier.

employees and does business in 180 countries. NCR is a trademark of NCR Corporation in the United States and

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR SelfServ and APTRA are either registered trademarks or trademarks of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.



17FIN4425-DDD-1017 ncr.com

